

Material Safety Data Sheet

Inducoat BV

Inducoat mould resistant coating flat white. Version 1.4 EN 1

Date 8/10/2007 Revisiondate : 8/02/2021

1. Identification of the substance/preparation and of the company/undertaking

Product name and/or code	: Inducoat mould resistant coating flat white.
Manufacturer	: Inducoat BV, PO Box 2776, 3800 GJ Amersfoort, the Netherlands.
Emergency Telephone	: Inducoat 033 456 23 94 : Telefax 033 456 25 94

2. Composition and information on ingredients This product is not classified to be dangerous according to Directive 1999/45/EC and its amendments, but contains dangerous components

Components	EINECS / C	AS- No	Symbol	s R-phrases	Concentration
2-octyl-2H-isothiazool-3-on	26530-20-1 /	247-761-7 / 613-112-00-5	ΤN	22,23/24,34,43 50/53	s < 0.01 %
Naphtha (petroleum), hydrodesulfurized, heavy	64742-82-1/	265-185-4	Xn N	10,65,51/53	< 2 %
3. Hazards identification					
Classification		: This product is not classified	d as dang	gerous.	
4. First aid measures					
General		: In all cases of doubt, or whe attention. Never give anything by mout		•	
Eye contact		: Check for and remove cont running water for at least 15			•
Skin contact		: Remove contaminated cloth with water and soap. Do not use solvents or th	•	nce. Wash skin	thoroughly
Inhalation		: Remove to fresh air. Keep If not breathing, irregular be provide artificial respiration nothing by mouth. If unconscious, place in reco	reathing or oxyge	or respiratory a n by trained pe	arrest occurs ersonnel. Give



Material Safety Data Sheet

Inducoat BV

Inducoat mould resistant coating flat Version 1.4 EN 1	white.	Date 8/10/2007 Revisiondate : 8/02/2021		
Ingestion	: If swallowed seek medical advice Safety Data Sheet. Keep person warm and at rest. De			
5. Fire-fighting measures.				
Extinguishing media	: Product is non-flammable.			
Special fire-fighting Procedures	: Cool closed containers exposed Do not release runoff from fire to			
6. Accidental release measures.				
Personal precautions	: Ventilate the area. In case of spill floors. Use personal protective equipment			
Spillage	: Contain and collect spillage with materials, e.g. sand, earth, vermicu place in container fro disposal a regulations. Do not allow to enter drains or wa with a detergents, avoid use of s In case of contamination of lakes, appropriate authorities in accordar	ulite, diatomaceous earth, and ccording to local atercourses. Clean preferably solvents. rivers or sewers, inform the		
7. Handling and storage				
Handling	: Apply material only in ventilated and eyes. Avoid inhalation of dust, arising from the application of th Eating, drinking and smoking. shou this material is handled, stored ar wash hands and face before eating Keep containers closed when no Comply with health and safety at the	particulates and spray mist ne product. uld be prohibited in the areas here nd processed. Workers should g, drinking and smoking. t in use.		
Storage	: Store in a well ventilated area, te ignition sources. Do not store bel with local regulations. Containers that have been opened kept upright to prevent spillage.	ow 0 °C. Store in accordance should be carefully resealed and		
8. Exposure controls /personal protec	tion			
General	· Provide adequate ventilation Wh	ere reasonably practicable, by		

 General
 : Provide adequate ventilation. Where reasonably practicable, by use of local exhaust ventilation and good general extraction. Otherwise wear suitable respiratory protection.

 Never eat, drink or smoke in work areas. Practice good personal hygiene when using this product, especially before eating, drinking,



Material Safety Data Sheet

Inducoat BV

Inducoat mould resistant coating flat white. Version 1.4 EN 1 $\,$

Date 8/10/2007 Revisiondate : 8/02/2021

smoking, using the toilet or applying cosmetics. Keep away from food, drink and animal foods.



Personal protective equipment

Respiratory system	In case of inadequate ventilation use appropriate certified espirators.
Hands	: For prolonged or repeated handling use gloves (nitrile, neoprene, latex rubber).
Eyes	: Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury. Use safety eyewear designed to protect against splash of liquids.
Skin and body	: Personnel should wear protective clothing.
9. Physical and chemical properties	
Physical state Colour Odour Flashpoint	: Viscous liquid. : White. : Characteristic odour. : Not applicable. Non-flammable, but will burn upon evaporation of the water contents. No usual hazard if involved in a fire.
Specific mass Viscosity pH	: 1.45 g/cm3 bat 20° C. : 150 poises. : 8.0 – 9.0.

10. Stability and reactivity

Stable under the recommended handling and storage conditions.

Keep away from oxidizing agents, strong alkalis and acids in order to prevent exothermic reactions.

Hazardous decomposition products : carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. Toxicological information

On this preparation itself no data are available. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

12. Ecological information

On this preparation itself no data are available. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for eco-toxicological properties accordingly.

13. Disposal considerations

Product

: Do not allow to enter drains, watercourses or soil. Do not remove with regular waste. Dispose of according to all state and local regulations.







The product is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA)

Sea	: according to IMDG	
Road	: according to ADR	
Rail	: according to RID	
Air	: according to IATA/ICAO	
15. Regulatory information		
Symbols	: not applicable.	
Risk Phrases	: not applicable.	
Safety Phrases	: S 2 Keep out of reach of children.	
	: S 13 Keep away from food, drink and animal feeding stuff.	
	: S 46 If swallowed, seek medical advice immediately and show this container or label.	
	: S 60 This material and/o its container must be disposed of as hazardous waste.	
Contains	: 2-octyl-2H-isothiazool-3-on. Might cause an allergic reaction.	
VOC value	: 30 gram/liter.	

16. Other information.

Full text of the R-phrases mentioned in section 2

2-octyl-2H-isothiazool-3-on	R22	Harmful if swallowed
and	R 23/24	Toxic by inhalation and in contact with skin
naphtha	R 34	Causes burns
	R 43	May cause sensitization by skin contact
	R50/53	Very toxic to aquatic organisms, may cause long-term adverse
		effects in the aquatic environment.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in
		the aquatic environment.
	R10	Flammable
	R65	Harmful: may cause lung damage if swallowed
Designation of the symbols in	т	Toxic
Section 2	Ν	Dangerous for the environment
	Xn	Harmful

The information in this sheet complies with EU regulations.

The information in his sheet is based on the state of technology and applicable national legislation and regulations on the date of issue.

The manufacturer reserves all rights to change the contents of this sheet without notice. In case of changes a new sheet will be issued.

The user has the obligation to check each time this sheet consulted, to check the date of publication . In case of a publication date older than 1 year user has to check with manufacturer whether the contents of this sheet are still valid.

Since the manufacturer has no control over the actual application conditions of the product, the user bear full responsibility for compliance with applicable legal and regulatory directives.

Final determination of suitability of any material is the sole responsibility of the user, the manufacturer does not accept any liability based on the contents of this Safety Data Sheet.